

Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Young Nails Inc.
1149 N. Patt St.
Anaheim, CA 92801
714.992.1411

FOR CHEMICAL EMERGENCY OR INGESTION 24/7
CALL INFOTRAC (USA) 1-800-535-5053 OR
INTERNATIONAL CALL COLLECT 1-352-323-3500

Name of Product: HEAVEN HELP ME

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS #	%	Hazard Symbol	Risk Phrases
Ethyl Acetate	141-78-6	25-35%	F, XI	R11, R36, R66, R67
Butyl Acetate	123-86-4	22-32%	F	R10, R66, R67
Isopropyl Alcohol	67-63-0	7-17%	F	R37, R11, R36, R67
Nitrocellulose	9004-70-0	5-15%	F	R11
Diacetone Alcohol	123-42-2	0-6%	XI	R36

3. HAZARDS IDENTIFICATION

- Flammability : Highly Flammable
- Inhalation : Prolonged inhalation may be harmful.
: Can cause drowsiness, headaches, nausea, vomiting and narcosis.
: May cause lung irritation.
- Skin : Mild skin irritant, can cause non-allergic contact dermatitis.
- Eyes : Eye irritant both liquid and vapor
- Ingestion : Causes gastro-intestinal irritation, nausea, vomiting and diarrhea.
: Kidney damage

Risk Phrases/Hazard Symbols: NOTE: Definition of listed Risk Phrases and Hazard Symbols (Section 2.) can be found in Section 15.

4. FIRST AID MEASURES

Inhalation	: Remove to fresh air. : Seek medical attention.
Skin	: Wash affected area with soap and water.
Eyes	: Irrigate with copious amounts of water. : Seek medical attention.
Ingestion	: Do not induce vomiting. SEEK IMMEDIATE MEDICAL ATTENTION

5. FIRE FIGHTING MEASURES

MAGNITUDE	APPLICABLE EXTINGUISHER TYPE
Small fire	Carbon Dioxide, foam or dry chemical extinguishers.
Large fire	Water or foam extinguishers, water fog.

note:- In all cases keep nearby containers cool by spraying with water.

Keep away from heat and sources of ignition

OSHA Flammability Class IB

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Use suitable protective clothing/equipment. Eliminate all sources of ignition. No Smoking.
Methods Of Cleaning Up	Contain spillage with absorbent. Mop up small spill Sweep up, use absorbent for larger spill
Environmental Precautions	Do not allow to enter water courses or drains Dispose in accordance with local regulation Local authorities should be advised if significant spill cannot be contained.

7. HANDLING AND STORAGE

Storage

Keep containers tightly closed, cool, dry, and away from sources of ignition, label containers
Eliminate possible point ignition sources, e.g. No smoking, Open flames, Use proper Bonding and Grounding.
Use electrical equipment rated for use with flammables.

Handling

No Smoking

Prevent static discharges.

Exposure by inhalation or skin contact should be minimized by good industrial hygiene.

Vapor is heavier than air, spreads along the ground.

Vapor can form an explosive mixture in air, prevalent in empty unclean drums/pails.

Use non-sparking tools when handling this material.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Levels

Substance	OSHA- PEL-TWA	ACGIH - TLV-TWA
Ethyl Acetate	400 ppm	400 ppm
Butyl Acetate	150 ppm	150 ppm
Isopropyl Alcohol	400 ppm	200 ppm
Nitrocellulose	Not established	Not established
Diacetone Alcohol	50 ppm	50 ppm

Ventilation and extraction of appropriate design is necessary to meet the above levels.

Personal Protection

Appropriate PPE should be worn – Check Local Regulations.

Eye Protection

Clothing / Uniforms

Respirator should be worn if the maximum exposure levels are surpassed

HMIS RATING

Hazard Rating: (0=least, 1=slight, 2=moderate, 3=serious, 4=severe)

HEALTH: 2 FIRE: 3 REACTIVITY: 1 PP: G

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Liquid

Boiling/melting Point: 75 – 80 ° C

Flash Point: - 4° C or 24° F Method: TCC (Tag Closed Cup)

Upper/lower explosion limits: Undefined

Water Solubility: Insoluble

Vapor Density: Heavier than air

Specific Gravity (H₂O=1): 0.95-0.97

10. STABILITY AND REACTIVITY

Stability: Stable under recommended storage conditions, affected by U.V., store away from direct sunlight.

Incompatible With: Strong oxidizing agents. Acids, Alkalines, and Peroxides

Hazardous Decomposition: Combustion of nitrocellulose may evolve nitrous oxide (poisonous) fumes. CO, CO₂, Nitrous Oxides, Smoke

Conditions to avoid: Flame, Electric spark, static and heat. Do not store @ Temperature Over 120°

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicity:- LD 50 Rat:- Undefined

Organic solvents in the product may lead to removal of lipid soluble elements of the skin leading to non-allergic dermatitis upon repeated prolonged contact.

Vapor from solvents may cause: ill effects to the renal system; central nervous system problems; irritation to the respiratory tracts and other various mucosal membranes.

12. ECOLOGICAL INFORMATION

Product should not be allowed to enter drains or water courses.

Used in large volumes, this product may incur the requirements of the Environmental Protection Act (pollution control/air). Environmental Protection Agency

13. DISPOSAL CONSIDERATIONS

Dispose of product in accordance with local, county, state, and federal government Regulations.

14. TRANSPORT INFORMATION

Proper Shipping Name : Paint
Technical Name : Nitrocellulose Lacquer(Ethyl Acetate, Butyl Acetate)
U.N. number : 1263
DOT Hazard Class : 3 (Flammable Liquid)
Packing Group : II
Flash Point : - 4°C or 24° F TCC (Tag Closed Cup)
ADR : Class 3; F1

15. REGULATORY INFORMATION

UNITED STATES FEDERAL REGULATIONS:

SARA: See section 2 for reportable material

SARA TITLE III: See Section 2

CERCLA: See Section 2

TSCA: - Components in this product have been verified as being on the TSCA Inventory and have been classified in accordance with the hazard criteria of the CFR and all information required.-

STATE REGULATIONS:

Proposition 65: None

EU Risk Phrases : R10 Flammable
R11 Highly Flammable
R20 Harmful by inhalation
R21 Harmful in contact with skin
R22 Harmful if swallowed
R36 Irritating to eyes
R37 Irritating to respiratory system
R38 Irritating to skin
R41 Risk of serious damage to eyes
R43 May cause sensitization by skin contact
R65 Harmful: may cause lung damage if swallowed
R66 Repeated exposure may cause skin dryness or cracking
R67 Vapors may cause drowsiness and dizziness.

EU Safety Phrases : S16 Keep away from sources of ignition- **No Smoking**
S23 Do not breathe vapor.
S25 Avoid contact with eyes.
S29 Do not empty into drains.
S33 Take precautionary measures against.

Hazard Symbols : Xn - Harmful
Xi - Irritant
F - Highly Flammable

NOTE: The appropriate Risk Phrases and Hazard Symbols pertaining to this product are listed Section 2.

16. FURTHER INFORMATION

This does not constitute a guarantee of product characteristics.

The information given is to the company's belief accurate and reliable at the date indicated.

No warranty, guarantee or representation to its accuracy, reliability or completeness is implied.